

13.12	2.15.09	22.08	.8.05	.11.99	DATE
CHANGE AS PER ECN 12-006	CHANGE AS PER ECN 09-186	CHANGE AS PER ECN 08-162	.8.05 CHANGE AS PER ECN 05-032	.11.99 CHANGE AS PER ECN 99-056	DESCRIPTION
Ш	$\Box$	0	В	≻	REV.

- 1. SHELL: MAT'L- PHOSPHOR BRONZE FINISH- TIN PLATE, OVER NICKEL PLATE
- 2. INSULATOR: MAT'L- GLASS FILLED LCP
- 3. CONTACTS: MAT'L- PHOSPHOR BRONZE
- FINISH- CONTACT AREAS-

4. ELECTRICAL SPECIFICATIONS: SOLDER TAIL- TIN PLATE, OVER NICKEL PLATE GOLD PLATE, OVER NICKEL

OPRATIONG TEMPERATURE: -25°C TO 85°C DIELECTRIC WITHSTANDING VOLTAGE: 500V AC CONTACT RESISTANCE: 30 milliohms MAX. INSULATION RESISTANCE: 100 Mohms MIN

SUPPLIED ON TRAY: 100 PCS PER TRAY **DURABILITY MIN.: 1500 cycles** 

## KEYSTONE ELECTRONICS CORP.

www.keyelco.com ● NEW HYDE PARK, NY 11040 ● Tel (516) 328-7500

## **USB A-TYPE HORIZONTAL SOCKET**

TOLERANCES INCH [MM] CODE DWG NO.  DECIMAL ± .010 [± 0.25 ] C 921  UNLESS OTHERWISE SPECIFIED
DWG NO.
RH.