

- ▶ Cable Ties
- ▶ Cable Ties with Fasteners
- ▶ Cable Tie Tools
- ▶ Clamps and Clips
 - Heatshrink Moulded Shapes
- ▶ Mounts
- ▶ Heavy Duty Mounts
- ▶ Wire Connectors
- ▶ Wiring Duct
- ▶ Wiring Protection
- ▶ Labels, Printers and Software
 - Pre-Terminated Networking
- ▶ Copper Network Solutions
- ▶ Fiber Network Solutions
- ▶ Jacks and Wall Plates
- ▶ Racks - Cable Management
- ▶ Surface Raceway Systems

T18R0UVC2

Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66UV, Black, 100/pkg

Article Number: 111-01914

Part Number: T18R0UVC2

Type: T18R

- ➔ Find a Distributor
- ➔ Order Samples
- ➔ Get Technical Drawings



→ **Base Data**

Part No.	T18R0UVC2
Type	T18R
Color	Black (BK)
Features	• UV stabilized cable ties contain an inhibitor which prolongs the life of the tie in UV exposures . • Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Application Method	Quick, simple fixing by hand or with HellermannTyton tensioning tools
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Typical Application	Used to bundle and secure wire and cable.
Variant	Inside Serrated

➔ Product Dimensions

Min. Tensile Strength	18.0lbs / 80.0N
Length (L)	4.0" / 100.0mm
Width (W) (imperial)	0.1"
Width (W)	2.45mm
Min. Ø Bundle	0.06" / 1.5mm
Max. Ø Bundle	0.86" / 22.0mm

➔ Material and Specifications

Material	Polyamide 6.6 UV-resistant (PA66UV)
US MILSPEC	MS3367-4-0
CSA Certified	No
Flammability	UL94 V2
Material Specification	RoHS / HF
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	 RoHS
Specification	UL ZODZ2.E64139 / MIL 53421

UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No

 Logistic and Packaging

Packaging Type	bag
Pkg. Qty.	100
Carton Qty.	10000
EAN code	4031026423586
UPC	089306208877

[Find a Distributor](#)

[Get Product Samples](#)

[Get Technical Drawings](#)