

- ▶ [Cable Ties](#)
- ▶ [Cable Ties with Fasteners](#)
- ▶ [Cable Tie Tools](#)
- ▶ [Clamps and Clips](#)
- ▶ [Heatshrink Moulded Shapes](#)
- ▶ [Mounts](#)
- ▶ [Heavy Duty Mounts](#)
- ▶ [Wire Connectors](#)
- ▶ [Wiring Duct](#)
- ▶ [Wiring Protection](#)
- ▶ [Labels, Printers and Software](#)
- ▶ [Pre-Terminated Networking](#)
- ▶ [Copper Network Solutions](#)
- ▶ [Fiber Network Solutions](#)
- ▶ [Jacks and Wall Plates](#)
- ▶ [Racks - Cable Management](#)
- ▶ [Surface Raceway Systems](#)

T120R0HSC2

Heavy Duty Cable Tie, 15.2" Long, 120lb Tensile Strength, PA66HS, Black, 100/pkg

Article Number: 111-12057

Part Number: T120R0HSC2

Type: T120R

➔ [Find a Distributor](#)

➔ [Order Samples](#)

➔ [Get Technical Drawings](#)

 [Share](#)

➔ **Base Data**

Part No.	T120R0HSC2
Type	T120R
Color	Black (BK)
Features	• Heat stabilized heavy duty cable ties provide excellent resistance to high heat exposures. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Application Method	Quick, simple fixing by hand or with HellermannTyton tensioning tools
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Typical Application	Used to bundle and secure wire and cable.
Variant	Inside Serrated

➔ **Product Dimensions**

Min. Tensile Strength	120.0lbs / 535.0N
Length (L)	15.2" / 387.0mm
Width (W) (Imperial)	0.3"
Width (W)	7.6mm
Min. Ø Bundle	0.2" / 5.0mm
Max. Ø Bundle	4.1" / 105.0mm

➔ **Material and Specifications**

Material	Polyamide 6.6 heat stabilized (PA66HS)
CSA Certified	No
Flammability	UL94 V2
Material Specification	HF / RoHS
Operating Temperature	-40 °F to +257 °F (-40 °C to +125 °C)
ROHS Conformity	 RoHS
Specification	MIL 53421 / UL ZODZ2.E64139
Specification	VG U48/04103
UL Listed (US and	Yes

Canada)

UL Recognized (US and Canada)

Yes

 Logistic and Packaging

Packaging Type

bag

Pkg. Qty.

100

Carton Qty.

1000

EAN code

4031026414560

UPC

089306175629

[Find a Distributor](#)

[Get Product Samples](#)

[Get Technical Drawings](#)

[Home](#) | [About HellermannTyton](#) | [Products](#) | [Careers](#) | [Contact](#) | [Terms](#)

© HellermannTyton North America 2011 | [TS16949](#), [ISO 9001](#) and [ISO 14001](#) Certified
7930 N. Faulkner Rd. Milwaukee, WI 53224-9517 | Fax: 800-848-9866 | Phone: 800-537-1512