



WC3-9

Clip-Tag marked 9, .075"-104", Nylon, White, 300/Pkg

Article Number: 560-10235

Part Number: WC3-9

Type: WC3

Base Data


| | |
|----------------------------|---|
| Part No. | WC3-9 |
| Type | WC3 |
| Color | White (WH) |
| Features | <ul style="list-style-type: none"> • Clip-Tags are snap-on markers which slip easily on wire and cable. • Markers are non-adhesive and come on a plastic wand for trouble free installation. • Interlocking design of these markers help to keep them aligned and readable. • Clip-Tags have an opening on one end which means that they can be used on pre-terminated and pre-installed wires attached to terminal blocks. |
| Application Method | Clip-Tags are applied by placing the flared end of the wand over the wire and then pushing the marker over the flare and on to the wire with the tip of the finger. |
| Color of Print | Black (BK) |
| Marking Text | 9 |
| Typical Application | Clip-Tags are designed to mark pre-terminated wires, pre-installed wires and wires connected to terminal blocks. Markers are open on one side so that they can be attached directly to cable. |

Product Dimensions

| | |
|--------------------------------|-----------------|
| Length (L) | 0.125" / 3.19mm |
| Core diameter from / to | 1.9 - 2.65mm |
| Min. Outside Ø | .075" |
| Min. Diameter Ø | 1.9mm |
| Max. Outside Ø | .104" / 2.65mm |

Material and Specifications

| | |
|-----------------|----------------------|
| Material | Polyamide 6.6 (PA66) |
|-----------------|----------------------|

| | |
|------------------------------|--|
| Operating Temperature | -40 °F to +185 °F (-40 °C to +85 °C) |
| ROHS Conformity |  RoHS |

Logistic and Packaging

| | |
|-------------------------------|--------------|
| Packaging Type | pack |
| Pkg. Qty. | 300 / 300 |
| Carton Qty. | 300 |
| Minimum Order Quantity | 300 |
| UPC | 089306111399 |

© HellermannTyton North America 2011 | [TS16949](#), [ISO 9001](#) and [ISO 14001 Certified](#)
7930 N. Faulkner Rd. Milwaukee, WI 53224-9517 | Fax: 800-848-9866 | Phone: 800-537-1512