



Part Number . . .

XKN.M08.GLLG

Size/Series XPN / XP

[Request a quote](#)

MECHANICAL DETAILS

Shell Style/Model XK...XP*: Fixed socket, key (N) or keys (P, S and T), grey, with two nuts (back panel mounting)

Keying 3 key (alpha=30, plug: male contacts, receptacle: female contacts)

Housing Material

Cable Fixing J : 0 - 0 mm

Variant G : Gray front nut

	A	L	N	e
mm.	18.5	25.7	23.5	M14x1
in.	0.73	1.01	0.93	

PERFORMANCE DETAILS

Insert Configuration M08 : 8 Low Voltage

Insulator L: PEEK

Specifications

Contact Type: Solder

Max. Matings: 1000

Contact Dia.: 0.9 mm (0.0354in)

Bucket Dia.: 0.8 mm (0.032in)

Max. Solid Conductor: 0.36 mm^2 (AWG 22)

Max. Stranded Conductor: 0.36 mm^2 (AWG 22)

R (max): 8.5 mOhm

OTHER CHARACTERISTICS

F ret (average): 130 N

Working temperature: -50 deg C to + 170 deg C

IP Rating 50

Catalog

[Copyright](#) [Privacy policy](#) [Product safety](#)

http://intra.lemo.ch/PartSearch/SinglePartDisplay/cFMCAAI3cwdtR2Z5cUxUUWVUIUwA... 2/21/2012