

Part Number . . . 
ERN.00.250.CTL

Status Active

Size/Series 00 / 00

Matching FFA.00.250.CTAC29

[Request a quote](#)
MECHANICAL DETAILS

Shell Style/Model ERN*: Fixed receptacle, nut fixing, with earthing tags

Keying Circular (can rotate)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing J : 0 - 0 mm

Variant :

	A	L	Weight
mm.	8	15	2.8
in.	0.31	0.59	0.11

PERFORMANCE DETAILS

Insert Configuration 0.25 : 1 Coax (50 Ohm)

Insulator T: PTFE

Specifications

Contact Type: Coaxial 50 Ohm (Solder)

Max. Matings: 5000

Contact Dia.: 0.7 mm (0.028in)

Bucket Dia.: 0.6 mm (0.024in)

R (max): 6.1 mOhm

Vtest: 2100 V (AC), 3000 V (DC)

Rated Current: 4 A (AC/DC)

Impedance: 50 Ohm

VSWR: 1.09 + 0.11 * f/GHz

OTHER CHARACTERISTICS

Endurance (Shell) 5000 mating cycles

F ret (min): 100 N

IP Rating 50

Catalog

