REV.	DESCRIPTION	DATE	DESIGNED
1	Color part No. is added.	AUG. 3.2007	T.S



NOTE

1.Connector part:See the DWG. of ZE connector.

2.Quantity to be packaged:800pcs/reel

3.Leading tape length.



4.Cover tape peel strength:0.1~1N

(Peel speed:300mm/minute)



5.Material:Carrier tape;Polyester(PET)

Cover tape ;Polyester(PET)

Reel ;Flange;Polystyrene(PS)

Core ;Polypropylene(PP)

Polystyrene(PS)

6.Unless otherwise specified,

tolerances are ±0.3





SUCTION TAPE CONFIGURATION

Color	Part No.
Natural	BM( )-ZESS-TBT (LF)(SN)
Moss green	BM( )-ZEMGS-TBT (LF)(SN)

Cir-cuits	Dimensions					
	A	B	C	D	E	F
2	7.9	2.2	24.0	11.5	25.5	7.3
3	9.4	3.7	24.0	11.5	25.5	8.8
4	10.9	5.2	24.0	11.5	25.5	10.3
5	12.4	6.7	24.0	11.5	25.5	11.8
6	13.9	8.2	24.0	11.5	25.5	13.3

No.	PART NAME	MATERIAL	SURFACE FINISH	REMARKS

SIZE	UNIT	SCALE	PROJECTION	DATE
A2	METRIC	3:1		AUG. 3.2007

APPROVED	CHECKED	DESIGNED	DRAWN
S.K		T.S	A.S

CUSTOMER

SERIES NAME	ZE CONNECTOR EMBOSSED-TAPING
PART No.	BM( )B-ZE( )S-TBT (LF)(SN)
DRAWING No.	KRD-41787 R1

JST J.S.T.MFG.CO., LTD.

EC4113-2

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T.
AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.