

TAPING STYLE B : 4Pos AND MORE

[illegible]

TAPING STYLE A : 2Pos, 3Pos

Technical drawing of a tape reel blank with dimensions and assembly instructions.

Dimensions and Tolerances:

- 12.7 ± 1
- 12.7 ± 0.3 PITCH
- 6.35 ± 1.3
- 5 ± 1
- 3.5 ± 1
- 12.7 ± 1
- 12.7 ± 1

Assembly Instructions:

- つづら折り位置 (FOLDING POSITION)
- コネクタ引き出し方向 TOP OF REEL (Connector pull-out direction TOP OF REEL)
- 100 程度 空部 (APPROX. 100 WITHOUT CHARGE)
- つづら折り曲げ範囲 (FOLDING RANGE)
- 12.7 PITCH × 26 = 330.2
- 25個連続してテーピング後1個ブランクの繰り返し (TO REPEAT TAPING ONE PIECE BLANK AFTER TAPING CONTINUOUSLY 25 CONN)

Notes:

- 空部 100 WITHOUT
- 0.6
- THIS DRAWING IS A CONTROLLED

1.5 MAX

0.6

SECT C-C

Technical drawing of the back of a card. The drawing shows a perspective view of the card with a cross-section line. Dimensions are indicated as follows:

- Top width: 2.0 MAX
- Height: ± 1 (37.1)
- Bottom width: (0.375)

Labels at the bottom of the drawing:

- 台紙厚 (Card thickness)
- BACKING P

- ① 累積ピッチ公差は20ピッチで±1.0mmとする
- ② 測定位置はポスト先端中心とする
- ③ 貼り付けテープは台紙からはみ出さないこと
- ④ 測定位置はテーピングの上端位置とし、リード線の中心線との間隔とする
- ⑤ 12.7 PITCH 寸法の中心値を基準とする

- ① ACCUMULATING TOLERANCE : ±1.0mm/20 PITCH
- ② MESURING POINT : AT TOP OF POST
- ③ TAPE MUST NOT PROTRUDE FROM BACKING PAPER
- ④ MESURING POINT, THE TOP OF TAPING AND THE CENTER LINE OF LEAD WIRE
IN BETWEEN
- ⑤ BE BASED ON THE CENTER 12.7mm PITCH DIMENSION

基板取付け寸法
P.C.B MOUNTING LAYOUT
(適用基板厚 1.6mm)
(APPLICABLE P.C.B THK 1.6mm)

Technical drawing showing a cross-section of a component. The drawing includes dimensions for the width of the top section (E), the width of the base section (2.5±1), the width of the middle section (6.35±1.3), and the width of the bottom section (12.7±0.3PITCH). A note (4) is present in the bottom right corner.

2極
2 POS

つづら箱
AMMO PACK

型番はシート2枚目参照
FOR PART NO. SEE SEET 2 OF 2

尺度	2:1	1	2	D
----	-----	---	---	---

表 2
TABLE 2

部品番号 PARTS NO	名称 PARTS NAME	材質、表面処理 MATERIAL & FINISH
①	ヘッダーハウジング HEADER HOUSING	66ナイロンガラス強化(UL94V-0) 66 NYLON GLASS FILLED
②	ポストコンタクト POST CONTACT	錫めっき済黄銅 PRE TIN BRASS
③	ラジアルピン RADIAL PIN	錫めっき済黄銅 PRE TIN BRASS
④	ラジアルテープ RADIAL TAPE	感熱紙 THERMAL PAPER
⑤	台紙 BACKING PAPER	クラフト紙 CRAFT PAPER

ラジアルピン, ポストコンタクト位置 ○:ラジアルピン, *:ポストコンタクト, -:ピン抜き																	
				○	-	○	3	A	900	WITHOUT	10.0	RED	2	5.0	6-1376500-2		
				○	-	○	3	A	900	WITHOUT	10.0	NATURAL	2	5.0	5-1376500-2		
*	*	○	*	○	*	*	7	B	450	WITHOUT	20.0	RED	7	2.5	6-1376492-7		
*	*	○	*	○	*	*	7	B	450	WITHOUT	20.0	NATURAL	7		5-1376492-7		
	*	*	○	*	○	*	6	B	450	WITHOUT	17.5	BLUE	6		7-1376492-6		
	*	*	○	*	○	*	6	B	450	WITHOUT	17.5	RED	6		6-1376492-6		
	*	*	○	*	○	*	6	B	450	WITHOUT	17.5	NATURAL	6		5-1376492-6		
		*	○	*	○	*	5	B	450	WITHOUT	15.0	BLUE	5		7-1376492-5		
		*	○	*	○	*	5	B	450	WITHOUT	15.0	RED	5		6-1376492-5		
		*	○	*	○	*	5	B	450	WITHOUT	15.0	NATURAL	5		5-1376492-5		
			*	○	*	○	4	B	450	WITHOUT	12.5	BLUE	4		7-1376492-4		
			*	○	*	○	4	B	450	WITHOUT	12.5	NATURAL	4		5-1376492-4		
				○	*	○	3	A	900	WITHOUT	10.0	RED	3		6-1376492-3		
				○	*	○	3	A	900	WITHOUT	10.0	NATURAL	3		5-1376492-3		
					○	○	2	A	900	WITHOUT	7.5	BLUE	2		7-1376492-2		
					○	○	2	A	900	WITHOUT	7.5	RED	2		6-1376492-2		
					○	○	2	A	900	WITHOUT	7.5	NATURAL	2	2.5	5-1376492-2		
7	6	5	4	3	2	1	ハウジング			テーパーピン	数量	BOSS	寸法 E	色	極数	ピッチ	型番
回路番号							極数			仕様		ラジアルピン ヘッダーアッセンブリ					

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
単位: 耗
MM

TOLERANCES UNLESS
OTHERWISE SPECIFIED:
一般公差

0 PLC ±—
1 PLC ±—
2 PLC ±—
3 PLC ±—
4 PLC ±—
ANGLES ±—

MATERIAL
材料

FINISH
仕上

DWN
—
CHK
—
APVD
—

PRODUCT SPEC
製品規格
—

APPLICATION SPEC
取付適用規格
—

WEIGHT
—

tyco
Electronics

Tyco Electronics AMP K.K.
Kawasaki, Japan

NAME
名称

2.5mmPITCH シグナルメイト コネクタ オンテープヘッダ(V-TYPE)
2.5mmPITCH SIGNAL MATE CONN ON TAPE HEADER(V-TYPE)

SIZE
A3

CAGE CODE
00779

DRAWING NO
番号
1376492

RESTRICTED TO
—

CUSTOMER DRAWING

SCALE
尺度
—

SHEET
2 OF 2

REV
D